




+1-469-708-8745

sales@moonshotUS.com

www.moonshotUS.com



# Crypto Leviathan V2



## V2 Upgrades

- More robust
- 4KV/10KA surge protection
- Up to 4/0
- Larger terminal block accepts up to 4/0
- Field repairable breakers & terminal block

### GENERAL

Part Number MS-PDU2-D24  
 Power 120KW  
 Agency Approvals ETL LISTED

### INPUT

Input Voltage 415V, 3 phase WYE  
 Input Current 160A per phase (480A total)  
 Surge Protection 4KV / 10KA  
 Overvoltage Rating Category 3

### OUTPUT

Outlet Type C19 (IEC 320-2-2/J)  
 Outlet Count 24  
 Outlet Voltage 230-250V  
 Output Current 20A per outlet  
 Protection 25A breaker per outlet. Breaker is UL1077 rated


### ENVIRONMENTAL

Operating temp 0-40°C ambient  
 Input wire size 4/0 Maximum  
 Input wire type Strand classes:  
 B,C (standard building wire)  
 G,H,I (DLO), K (flexible wire)  
 no ferrules needed for any strand class

### DIMENSIONS

Weight 21 lbs  
 Depth 4.23"  
 Width 5.28"  
 Length 45.88" (not including mounting tabs)

# Crypto Leviathan V2 SMART



## V2 Upgrades

- More robust
- 4KV/10KA surge protection
- Up to 20A per outlet
- Larger terminal block accepts up to 4/0
- Field repairable breakers & terminal block

## V2 Smart Only Upgrades

- Individual outlet monitoring
- Harmonic detection: Aggregate line monitoring (L1, L2, L3, N)
- Upgraded long life 30A relays

### GENERAL

Part Number MS-PDU2-S24  
 Power 120KW  
 Agency Approvals ETL LISTED

### INPUT

Input Voltage 415V, 3 phase WYE  
 Input Current 160A per phase (480A total)  
 Surge Protection 4KV / 10KA  
 Overvoltage Rating Category 3

### OUTPUT

Outlet Type C19 (IEC 320-2-2/J)  
 Outlet Count 24  
 Outlet Voltage 230-250V  
 Output Current 20A per outlet  
 Protection 25A breaker per outlet. Breaker is UL1077 rated

### ENVIRONMENTAL

Operating temp 0-40°C ambient  
 Input wire size 4/0 Maximum  
 Input wire type Strand classes:  
 B,C (standard building wire)  
 G,H,I (DLO), K (flexible wire)  
 no ferrules needed for any strand class

### DIMENSIONS

Weight 21 lbs  
 Depth 4.23"  
 Width 5.28"  
 Length 45.88" (not including mounting tabs)


### HARDWARE CAPABILITIES

Voltage monitoring Yes, one per phase (L1, L2, L3)  
 Current monitoring Individually measured per-outlet  
 Harmonic Detection: Aggregate Line Monitoring (L1, L2, L3, N)  
 Outlet control Each outlet individually controllable  
 Turn on/Turn off  
 Pulse  
 Measurements Line Voltage  
 Power  
 Energy used  
 Harmonic current  
 Current: L1, L2, L3, N  
 Ethernet 10/100/1000  
 Network User interface Front panel OLED display  
 Two pushbuttons  
 Beeper

### SOFTWARE FEATURES

Interface Web page  
 API

# Crypto Lunariss SMART



## Key Feature

- Supports M56 Miner

### GENERAL

Part Number MS-PDU-S9L-M56  
 Power 146KW  
 Agency Approvals ETL (pending)

### INPUT

Input Voltage 415V-480V, 3 phase WYE  
 Input Current 180A per phase (480A total)

### OUTPUT

Outlet Type SA2-30  
 Outlet Count 9  
 Outlet Voltage 480V  
 Output Current 20A per outlet  
 Protection 20A breaker per outlet. UL489, 65kaic

### ENVIRONMENTAL

Operating temp 0-40°C ambient  
 Input wire size 250MCM Maximum, AL9CU  
 Input wire type Strand classes:  
 B,C (standard building wire)  
 G,H,I (DLO), K (flexible wire)  
 no ferrules needed for any strand class

### DIMENSIONS

Weight 30 lbs  
 Depth 7.40"  
 Width 7.98"  
 Length 58.90" (not including mounting tabs)

### HARDWARE CAPABILITIES

Voltage monitoring Yes, one per phase (L1, L2, L3)  
 Current monitoring Individually measured per-outlet  
 Outlet control Each outlet individually controllable  
 Turn on/Turn off  
 Pulse  
 Measurements Line Voltage  
 Power  
 Energy used  
 Current: L1, L2, L3, N  
 Ethernet 10/100/1000  
 Network User interface Front panel OLED display  
 Two pushbuttons  
 Beeper

### SOFTWARE FEATURES

Interface Web page  
 API

Moonshot making the impossible possible.